GC Application ID No.: 1328



Diesel Fuel Oil No. 2

| Zebron [™] ZB-1, GC Cap. Column 30 m x 0.25 mm x 0.25 µm, Ea 100% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 µm 7HG-G001-11 40°C (2 min) to 320°C @ 6°C/min (hold 5 min) | | | | Contracted Daily and Participants und formy Sales of Charles | | |
|--|---|---|--|---|--|--|
| Split 100:1 1 µL @ 2 | 50°C | | | D | 2007 - 2009 RDD TOD Avers | |
| | 20 | 30 | | | Zebren | |
| 10 | 20 | 30 | 40 | 50 | /11/1 | |
| | Zebron™ ZB-1, GC C 100% Dimethylpolysi 30 meters x 0.25 mm 7HG-G001-11 40°C (2 min) to 320° Constant Flow Hydrog Split 100:1 1 µL @ 2 | Zebron [™] ZB-1, GC Cap. Column 30 m : 100% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 µm 7HG-G001-11 40°C (2 min) to 320°C @ 6°C/min (hol Constant Flow Hydrogen, 1.23 mL/min Split 100:1 1 µL @ 250°C Flame Ionization (FID) (325°C) | Zebron [™] ZB-1, GC Cap. Column 30 m x 0.25 mm x 0.25 100% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 µm 7HG-G001-11 40°C (2 min) to 320°C @ 6°C/min (hold 5 min) Constant Flow Hydrogen, 1.23 mL/min Split 100:1 1 µL @ 250°C Flame Ionization (FID) (325°C) | Zebron [™] ZB-1, GC Cap. Column 30 m x 0.25 mm x 0.25 μm, Ea 100% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 μm 7HG-G001-11 40°C (2 min) to 320°C @ 6°C/min (hold 5 min) Constant Flow Hydrogen, 1.23 mL/min Split 100:1 1 μL @ 250°C Flame Ionization (FID) (325°C) | Zebron [™] ZB-1, GC Cap. Column 30 m x 0.25 mm x 0.25 µm, Ea 100% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 µm 7HG-G001-11 40°C (2 min) to 320°C @ 6°C/min (hold 5 min) Constant Flow Hydrogen, 1.23 mL/min Split 100:1 1 µL @ 250°C Flame Ionization (FID) (325°C) Pro | |

ANALYTES:

1 Diesel fuel

©2025 Phenomenex Inc. All rights reserved.

Phenomenex products are available worldwide.

www.phenomenex.com.cn

For more information contact your Phenomenex Representative at info@phenomenex.com